

# RICOH

# Caplio<sup>★</sup> 500SE

DIGITAL CAMERA



**GPS  
Compatible**

**Bluetooth<sup>®</sup> Built-in  
IEEE802.11b/g Ready** (model W only)

Effective <b>8.13</b> megapixel CCD	<b>28mm</b> wide & zoom	Optical Digital <b>3X 4X</b> zoom	Impact resistance <b>1m</b> (up to 1m drop)
-------------------------------------	-------------------------	-----------------------------------	---


## Wireless & Tough

Wireless

Wireless communications with various devices  
— Built-in **Bluetooth<sup>®</sup>** & **Wireless LAN<sup>\*</sup>**

Ver.2.0+EDR IEEE802.11b/g \*model W only

Easily transfer photo data to PCs and other devices supporting Bluetooth<sup>®</sup> and/or wireless LAN. By simplifying the process of transferring data, this feature greatly improves work efficiency.



Add location information to your photo data by connecting with a **Bluetooth<sup>®</sup>** equipped **GPS** device

Connect Caplio 500SE wirelessly with a Bluetooth<sup>®</sup> compatible GPS device to add location information to your photo data. This feature is especially useful in disaster situations and when managing building construction data. No complicated settings are required: just wirelessly connect the GPS device. Caplio 500SE automatically recognizes it the next time their power is turned




Photo is simulated. Actual appearance may differ.

Toughness

**Tough enough to withstand being dropped from a height of 1 meter**

Armored glass protects the lens covering and various reinforcements protect key components throughout the body of this lightweight camera. The result is an impressive 1-meter impact resistance and full compliance with U.S. Department of Defense MIL-STD-810F test standards.

**Excellent water, dust and cold resistance in severe work environments**

Since the body meets JIS Class 7 Protection Standards, you can freely wash dirt off the camera, shoot in rainy conditions, and even shoot 1 meter under water\*. The Caplio 500SE is also extremely resistant to dust and sand, thanks to full compliance with JIS Class 5 Protection Standards. Moreover, weather as cold as -10°C is no problem. With the Caplio 500SE, you can shoot in some of the world's toughest weather. \*For less than 30 minutes

# Compact and convenient, with all the features you need for field work.

**Caplio**  
**500SE**  
model W / model B

## Camera shake blur reduction

Caplio 500G wide effectively reduces camera shake blur by combining high ISO settings with fast shutter speeds. Now you can shoot with greater confidence in dark situation

## Powerful built-in flash

The built-in flash unit allows clearer shooting in a wider range of situations. Its powerful illumination extends 10 meters in wide-angle shots and 6.5 meters in telephoto shots

## Large, easy-to-view 2.5-inch LCD screen

The large LCD screen features an anti-reflection coating for clearer viewing in daylight outdoors. You can easily adjust screen brightness to optimize image clarity. There is also an optical viewfinder, so you can use whichever is right for the situation, for more reliable photography.



## Wide coverage with 28mm wide-angle zoom lens

Ricoh's 28mm wide-angle zoom lens can capture larger areas than the 35mm lenses of conventional digital cameras. When there is limited space to maneuver, you can more easily capture an entire building or construction site with Caplio 500SE

## Vivid 1cm macro photography

Capture subjects as close as 1cm away in the macro wide-angle mode or 10cm away in the tele-macro mode. The built-in flash unit illuminates subjects as close as 20cm from the camera

## Large buttons and dials

All buttons and dials are large enough to ensure you can easily operate the camera even when wearing gloves



## Memo function for more convenient data management

Keep memos as part of your photo information. Memos are particularly handy for distinguishing numerous similar photographs and can dramatically heighten management efficiency

## Barcode memo function for temporary memos (model W only)

Shoot one-dimensional barcodes with the Caplio 500SE and register the barcode photos as temporary memos

### Caplio 500SE Major Specifications

Item	Description
CCD	Effective 8.13 million pixels (8.30 million square pixels), 1/1.8-inch primary-color CCD
Lens	Focal length f: 5.8-17.4mm (equivalent to 28-85mm for 35mm film cameras) Step-zoom intervals: 4 steps (28mm, 35mm, 50mm, 85mm) Aperture F: 2.5 (W)-4.3 (T)
Recording Media	SD Memory Card™ (3.3V 32/64/128/256/512MB/1GB), Multi Media Card™, Built-in Memory 26MB
Recording Mode	Still mode (Continuous, S-Continuous, M-Continuous), Scene mode (High-sensitivity, Fire, Skew Correction, Text, Zoom Macro), Motion mode, Sound mode
LCD Monitor	2.5" translucent amorphous silicon TFT LCD (approx. 153,000 pixels)
Dimensions (WxDxH)	133.0 x 78.5 x 74.0mm (excluding projections)
Weight	Approx. 430g (excluding battery, SD Memory Card, hand strap) Accessories (battery, hand strap) approx. 50g
Power Source	Rechargeable battery (DB-43) x 1, AA battery x 2, AC adaptor (AC-4d)
Bluetooth® specifications	Communication scheme: Bluetooth® standard version 2.0+EDR Output: Bluetooth® standard Power Class 2 Supported Bluetooth® profiles: BIP, OPP, SPP
Wireless LAN specifications (model W only)	Interface standard: IEEE802.11b/g Security: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES)

### Caplio 500SE Optional Accessories

Accessory Name	
Wide conversion lens: DW-5	Battery Charger: BJ-2e
Rechargeable Lithium-Ion Battery Set (DB-43+BJ-2e): BS-3e	AC Adapter: AC-4d
Rechargeable Lithium-Ion Battery: DB-43	Soft Case: SC-500

• The Bluetooth® word mark and logo are registered trademarks of Bluetooth SIG, Inc. Bluetooth® technology is used by Ricoh Co., Ltd. under licensing agreement with Bluetooth SIG, Inc. • Caplio is the registered trademark of Ricoh Co., Ltd. • Microsoft, Windows and Direct X are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. • Apple, Macintosh and Mac OS are registered trademarks or trademarks of Apple Computer Inc. in the U.S. and/or other countries. • The SD logo is a trademark. • Compatible with EPSON PRINT Image Matching III. • All other trademarks mentioned herein are the property of their respective owners.



For more information, visit:

[http://www.ricoh.com/r\\_dc](http://www.ricoh.com/r_dc)

# RICOH

**RICOH COMPANY, LTD.**  
3-2-3, Shin-yokohama  
Kohoku-ku, Yokohama-shi 222-8530, Japan  
Phone: 045-477-1738 Fax: 045-477-1797 [http://www.ricoh.com/r\\_dc](http://www.ricoh.com/r_dc)

**RICOH EUROPE B.V. (PMMC EUROPE)**  
Oberrather Straße 6, D-40472  
Düsseldorf, Germany  
Phone: 0211-6546-0 Fax: 0211-6546-308 <http://www.ricohpmmc.com>

**RICOH UK LTD. (PMMC UK)**  
Ricoth House, 1 Plane Tree Crescent, Feltham,  
Middlesex, TW13 7HG, England  
Phone: 0208-261-4000 Fax: 0208-261-4220

**RICOH FRANCE S.A. (PMMC FRANCE)**  
383, Avenue du Général de Gaulle – BP 307-931-13  
Clamart Cédex, France  
Phone: 01-4094-3267 Fax: 01-4094-3276

**RICOH ESPANA, S.A. (PMMC SPAIN)**  
Av. Litoral Mar, 12-14, 08005  
Barcelona, Spain  
Phone: 093-295-7600 Fax: 093-295-7605

**RICOH ITALIA S.p.A. (PMMC ITALY)**  
via Ponchielli, 3  
20063 Cernusco S/N Milano, Italy  
Phone: +39-02-92361217 Fax: +39-02-92361244

**RICOH HONG KONG LIMITED**  
Personal Multimedia Products Center  
21/F., Tai Yau Building, 181 Johnston Road, Wan Chai, Hong Kong  
Phone: 2862-2888 Fax: 2566-3647/2866-1120

**RICOH AUSTRALIA PTY. LTD.**  
8 Rodborough Road, Frenchs Forest, N.S.W. 2086 Australia  
Phone: 02-8977-1111 Fax: 02-8977-1100  
<http://www.ricoh.com.au>

**RICOH CORPORATION**  
5 Dedrick Place  
West Caldwell, NJ 07006 U.S.A.  
Phone: 1-800-Ricoh93 <http://www.ricoh-usa.com>